

Glue & Staple Assembly Standard Base Cabinet Assembly



**Assembly photos follow after instructions.*

Items you will need:

Wood glue
Screw gun
Razor knife
Soft Cloth
Air compressor
Staple gun
1" staples
Rubber mallet
Padded work area
½" X ¾" L-brackets (suggested)
½" screws (suggested)
Matching wax crayon (suggested)

Instructions

1. Unpack box.
2. Layout and identify pieces.
3. Start with the face frame. Place frame face down on padded work surface.
4. Run a bead of glue inside side grooves of face frame.
5. Install four L-brackets behind drawer opening and lower hinge. (Suggested)
6. Install sides flush with top and bottom with toe kick notch facing front of cabinet. Make sure finished sides are facing out.
7. Secure sides with ½" screws through L-brackets. (Suggested)
8. Run a bead of glue inside bottom groove of face frame and bottom groove in cabinet sides.
9. Slide cabinet bottom piece into the grooves, finished sides facing inward.
10. Using a rubber mallet tap cabinet bottom to be sure it fits securely into groove.
11. Always wipe off all excess glue before it dries with soft cloth.
12. Run a bead of glue inside bottom groove on back piece of cabinet and small bead along notch on both cabinet sides.

13. Align groove in cabinet back with bottom of cabinet make sure cabinet back is set securely into notches in sides of cabinet.
14. Install two screws into designated holes on back of cabinet using screws provided.
15. Secure back of cabinet with staples through sides of cabinet. (Make sure back is flush with sides at the top edge of cabinet.
16. Fill in staple holes with color matching wax crayon. Lightly buff out with soft cloth. (Suggested)
17. Allow glue to dry.
18. Install hinges into designated holes in back of door using screws provided.
19. Install door onto cabinet, using screws provided. Screw through hinges into pre-drilled holes.
20. Build drawer and insert. (See drawer instructions)
21. After cabinet installation, install cabinet shelves.
22. Open cabinet doors, push shelving clips into designated holes.
23. Push shelves into clips.
24. Toe kick provided is optional. Generally longer lengths of toe kick are purchased separately and used to give base cabinets a continuous toe kick.





